




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : G08B 13/14	A1	(11) International Publication Number: WO 99/19851 (43) International Publication Date: 22 April 1999 (22.04.99)
<p>(21) International Application Number: PCT/US98/18454</p> <p>(22) International Filing Date: 3 September 1998 (03.09.98)</p> <p>(30) Priority Data: 08/943,679 15 October 1997 (15.10.97) US</p> <p>(71) Applicant: ESCORT MEMORY SYSTEMS [US/US]; 3 Victor Square, Scotts Valley, CA 95066 (US).</p> <p>(72) Inventors: NICHOLSON, Mark; 3 Oak Creek Boulevard, Scotts Valley, CA 95066 (US). MONAHAN, Brian; 1865 Rodriguez Street, Santa Cruz, CA 95062 (US).</p> <p>(74) Agent: FRANCIS, Ralph, C.; Francis Law Group, 1946 Embarcadero, Oakland, CA 94606 (US).</p>		<p>(81) Designated States: AU, CA, JP, MX, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).</p> <p>Published <i>With international search report.</i> <i>With amended claims.</i></p> <p>Date of publication of the amended claims: 3 June 1999 (03.06.99)</p>

(54) Title: HIGH TEMPERATURE RFID TAG

(57) Abstract

A high temperature RFID tag (10,20) is described which has a survival temperature in the range of approximately -40°C to 300°C and an operating temperature of approximately -20°C to 200°C . The RFID tag comprises a housing (21) comprising a first thermally resistant material and having a base (24) and a top (22), and a circuit board substrate (26) which includes an IC circuit (28) and is disposed in a tag chamber (36), the substrate comprising a second thermally resistant material which is encapsulated in the housing. The thermally resistant materials exhibit a deflection temperature in a range of 287°C to 320°C .



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakistan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

AMENDED CLAIMS

[received by the International Bureau on 20 April 1999 (20.04.99);
original claims 1-12 replaced by new claims 1-16 (2 pages)]

1. A high temperature RFID tag, comprising:
a housing having base and a top, said base and said top forming a chamber therein,
5 said housing comprising a first thermally resistant material; and
a circuit board substrate disposed within said chamber, said substrate including an
integrated circuit, said substrate comprising a second thermally resistant material;
said housing and said substrate jointly having a survival temperature in the range
of approximately 220°C to 300°C.
- 10 2. The RFID tag of Claim 1, wherein said tag has an operating temperature in
the range of -18°C to 135°C.
3. The RFID tag of Claim 1, wherein said circuit board is substrate
encapsulated in said housing.
4. The RFID tag of Claim 3, wherein a high temperature epoxy is employed to
15 encapsulate said circuit board substrate.
5. The RFID tag of Claim 1, wherein said first thermally resistant material
comprises Teflon®.
6. The RFID tag of Claim 1, wherein said first thermally resistant material
comprises a Ryton® PPS compound.
- 20 7. The RFID tag of Claim 1, wherein said second thermally resistant material
comprises a polyimide.
8. The RFID tag of Claim 7, wherein said polyimide is pre-conditioned.
9. The RFID tag of Claim 1, wherein said second thermally resistant material
comprises a ceramic compound.

10. The RFID tag of Claim 1, wherein said housing has a substantially cylindrical shape.

11. The RFID tag of Claim 1, wherein said housing has a substantially square shape.

5 12. A RFID tag, comprising:
a housing and substrate assembly,
said housing having base and a top, said base and said top forming a chamber therein, said housing comprising a first thermally resistant material,
said substrate disposed within said housing chamber and including an integrated
10 circuit, said substrate comprising a second thermally resistant material,
said housing and substrate assembly having a survival temperature in the range of approximately 220°C to 300°C and an operating temperature range of approximately 18°C to 135°C,
said housing and substrate assembly being capable of exposure to cyclic changes in
15 temperature to and between said operating temperature and said survival temperature without substantially affecting the intended functions of the tag.

13. The RFID tag of Claim 12, wherein said substrate is encapsulated in said housing chamber with a high temperature epoxy.

14. The RFID tag of Claim 12, wherein said first thermally resistant material
20 comprises a Ryton ® PPS compound.

15. The RFID tag of Claim 12, wherein said second thermally resistant material comprises a pre-conditioned polyimide.

16. The RFID tag of Claim 12, wherein said second thermally resistant material comprises a ceramic compound.